

**Specifications Table: Two door vertical refrigerator and freezer**

Model	Total Interior Volume	Dimensions Standard Cut out	Cabinet to Front of Door	Flange Dimension	Panel dimension	DC Amp Draw 12/24VDC	Weight
RFU6200 DC WRFU6200 DC RFU6200 ACDC WRFU6200 ACDC	6.0 cu. ft.	47 3/4"H 20 1/4"W 20 1/2"D	2 1/2"	48 3/4"H 21"W	17 5/16"H 20 3/16"W	4.4/2.2	90lbs
RFU6800 DC WRFU6800 DC RFU6800 ACDC WRFU6800 ACDC	6.8 cu. ft.	47 3/4"H 20 1/4"W 21 1/2"D	2 1/2"	48 3/4"H 21"W	and 28"H 19 5/8"W same as RFU6200	4.4/2.2	98lbs
RFU8000 DC RFU80000 ACDC	6.8 cu. ft.	51 7/8"H 23"W 23"D	1"	53 3/8"H 24 5/16"W	17 5/16"H 19 5/8"W and 28"H 19 5/8"W	4.4/2.2	94lbs
RFU9000 DC RFU9000 ACDC	9.1 cu. ft.	52 7/8"H 23 1/4"W 22 3/4"D	1"	53 1/4"H 24 3/4"W	13 3/8"H 21 3/8"W and 29 5/8"H 21 3/8"W	5.6/2.8	110lbs

**Features:**

- Convenient freezer on the bottom
- Positive latch system
- Storage for tall bottles
- Shelves are a powder-coated wire for durability
- Reversible door swing
- Replaceable door panels for a custom finish to match your interior
- Backed with Nova\*Kool's Easy 2 Year Warranty Program on all components
- Environmentally sound 134a refrigerant
- CFC free urethane foam in cabinet and doors
- Magnetic door gaskets for positive seal
- Stainless fasteners & hinges used throughout
- Maintenance friendly & efficient static condenser
- Low battery protection to help prevent full discharge of batteries
- 100% of ventilation built into front of the RFU9000 with electrical access grille
- Voltage options:
  - DC only: 12 & 24VDC standard, optional 10-45VDC for special applications
  - AC/DC: 12 & 24 VDC and 100-240 VAC 50/60HZ
- Strongest mounting flanges in the industry available in white or black (flush or standard mounting)



RFU9000